

10 SERIES - DISTRIBUTION CABLE TRUNKINGS (SELECTION GUIDE)

RoHS

IP44

IK08



TRUNKINGS
(COVERS WITH 75MM WIDTH - L75)

Ref.

		Trunkings Characteristics				Isolated Cables Capacity				
Internal Dim.	Length	Internal Section (S)	Available Section (Su)	Max. Available ø	Max. Nr. Conductors H07 V-U					
(mm)	(m)	(mm ²)	(S:1,4) (mm ²)	(mm)	1,5mm ²	2,5mm ²	4mm ²	6mm ²		
90x50 without Divider				45	349	233	186	140		
90x50 with 1 Divider				40	169	113	90	68		
				40	169	113	90	68		
90x50 with 2 Dividers				25	65	43	35	26		
				30	197	131	105	79		
				25	65	43	35	26		
90x50 with Flush Mounting Box				—	188	126	100	75		
90x50 with Semi-Flush Mounting Box				—	240	160	128	96		
180x50 without Divider				45	354	236	189	141		
				45	354	236	189	141		
180x50 with 1 Divider				45	174	116	93	70		
				45	168	112	90	67		
180x50 with 2 Dividers				45	70	47	37	28		
				45	197	131	105	79		
				45	64	43	34	26		
180x50 with Flush Mounting Box				—	193	129	103	77		
180x50 with Semi-Flush Mounting Box				—	244	163	130	98		

NEW

NEW

10180 RBR

10290 RBR

