

13 SERIES - TRUNKINGS FOR PROTECTION OF CABLES AND PIPES (SELECTION GUIDE)



TRUNKINGS			Trunkings Characteristics				Cables, Pipes and Conductors Capacity				
			Internal Dim.	Length	Internal Section (S)	Available Section (Su)	Max. Available ø	Max. Nr. Conductors H07 V-U			
Ref.			(mm)	(m)	(mm ²)	(S: 1,4) (mm ²)	(mm)	1,5mm ²	2,5mm ²	4mm ²	6mm ²
25x30	13010 CBR		22x27	2,00	530,0	379	20	48	32	26	19
40x40	13020 CBR		37x37	2,00	1280,6	915	35	116	79	63	47
60x40	13030 CBR		56x37	2,00	1973,7	1410	35	180	122	97	73
60x60	13040 CBR		56x56	2,00	3101,7	2216	55	282	191	153	114
80x40	13050 CBR		73x36	2,00	2668,0	1906	35	243	164	132	98
80x60	13060 CBR		76x56	2,00	4192,0	2994	55	382	259	207	154
100x40	13070 CBR		96x36	2,00	3352,3	2395	35	305	207	166	123
100x60	13080 CBR		96x56	2,00	5272,3	3766	55	480	325	260	194