



Table1

Frequency (MHZ)	Attenuation(dB/100m)	NEXT(dB)	PSNEXT(dB)	
1	≤2.0	≥65.3	≥62.3	
4	≤4.1	≥56.3	≥53.3	
8	≤5.8	≥51.8	≥48.8	
10	≤6.5	≥50.3	≥47.3	
16	≤8.2	≥47.2	≥44.2	
20	≤9.3	≥45.8	≥42.8	
25	≤10.4	≥44.3	≥41.3	
31.25	≤11.7	≥42.9	≥39.9	
62.5	≤17.0	≥38.4	≥35.4	
100	≤22.0	≥35.3	≥32.3	

Table2

Frequency (MHZ)	ELFEXT(dB)	PSELFEXT(dB)	Delay(ns/100m)	Return Loss(dB)
1	≥63.8	≥60.8	≤570.0	≥20.0
4	≥51.8	≥48.8	≤552.0	≥23.0
8	≥45.7	≥42.7	≤546.7	≥24.5
10	≥43.8	≥40.8	≤545.4	≥25.0
16	≥39.7	≥36.7	≤543.0	≥25.0
20	≥37.8	≥34.8	≤542.0	≥25.0
25	≥35.8	≥32.8	≤541.2	≥24.3
31.25	≥33.9	≥30.9	≤540.4	≥23.6
62.5	≥27.9	≥24.9	≤538.6	≥21.5
100	≥23.8	≥20.8	≤537.6	≥20.1