57535-2



Copper Cable, category 5e, 4 pair, UTP, PVC, 24 AWG solid, 305 m pullbox, white

Product Classification

Portfolio	NETCONNECT®
Product Type	Twisted pair cable
Regional Availability	EMEA

Standards And Qualifications

EN50575 CPR Cable EuroClass Eca

Construction Materials

Jacket Material	PVC
Conductor Material	Bare copper
Insulation Material	Polyolefin

Dimensions

Cable Length	305 m	1000 ft
Diameter Over Jacket, nominal	5.100 mm	0.201 in

Electrical Specifications

ANSI/TIA Category	5e		
Transmission Standards	ANSI/TIA-568-C.2	CENELEC EN 50288-6-1	ISO/IEC 11801 Class E

Environmental Specifications

Operating Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
	· · · · · · · · · · · · · · · · · · ·

General Specifications

U/UTP (unshielded)
Pull box
4
Horizontal
White
24 AWG

page 1 of 2 January 29, 2019

©2019 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: January 9, 2019



57535-2

Conductor Type, singles	Solid
Conductors, quantity	8

Regulatory Compliance/Certifications

Agency RoHS 2011/65/EU CENELEC **Classification** Compliant EN 50575 compliant, Declaration of Performance (DoP) available



page 2 of 2 January 29, 2019

©2019 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: January 9, 2019

