



999101 4 Fiber Compact Termination Box

999101 Fiber Compact Termination Box is designed for use in residential and business applications for the termination of up to four fibers.

The wall box enables the installation of either a single Blown Tube cable using up to a 4 fiber blown unit or two 2 fiber ruggedised cables to be spliced to four SC pigtails (PC or APC), which connect to adapters at the base of the unit.

The unit can be quickly installed within an office, house or communication room environment.

Features and Benefits

- Ergonomic design.
- Ability to allow cables to enter from rear or bottom of the unit.
- All fibers are positively managed to maintain a 30mm minimum bend radius.
- Optional Removable rear entry cable management.
- Flip tray to allow access to pigtails and cable entry.
- Compact, low profile, wall mounted unit used for small and large business premises.
- Removable cover for easy access.
- Flame retardant LSZH material.
- Patchcords exit unit on bottom face and are protected by two protection covers.
- Standard color white. Other colors available on request.

Kit Contents

The 999101 4F Compact Termination Box is supplied with all of the components required to complete the installation of one Blown Fibre input cable, 4 splice protectors are supplied in the kit

Technical Data

- Number of input cable ports: 1
- Maximum input cable diameter (mm): 10mm
- Maximum Capacity: 4 Fibers
- Maximum no. of customer feeds: 4 Patchcords
- Required space envelope (mm): (l) 80 x (w) 120 x (d) 25
- Operating temperature: -20oC to + 50oC (5 to 95% RH)

Optional Items

(if required as separate items)

- Patchcords
- Adapters
- Pigtails
- Security Screw Kit

