

Unmanaged Network Switch 8*10/100/1000M RJ45

DK2000-1008G



Overview

The DK2000-1008G series unmanaged switches are Fast Ethernet switch designed for high forwarding network environment such as school, family, SMEs and mini monitoring. It has 8 10/100/1000Mbps adaptive Ethernet ports. All ports support wire-speed forwarding and the data rate is up to 1000Mbps. There is 4K lightning protection to ensure smooth and stable operation. Auto MDI/MDIX is also available. No configuration is required; it will instantly operate as soon as you power it up.

Features

- 8*10/100/1000M Ethernet port with auto-negotiation function
- Support 1000M speed rate, MDI/MDIX
- Support IEEE802.3x Flow control and back pressure control
- Each port has the complete LED Indicator light
- Support IEEE802.1d Spanning Tree
- Each port supports wire-speed switching ,64~1518 frame length can reach the wire speed
- Support high performance QoS function on each port
- Support multicast to avoid network congestion
- Support 5V voltage input
- Require no configuration and will instantly operate as soon as you power it up
- Use low-power consumption chips

Technical specification

Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX	IEEE802.3x Flow control IEEE802.1p QoS IEEE802.1d Spanning Tree
Ethernet Port	Connector: RJ45 Data Rate: 10/100/1000M Distance: 100m UTP Type: UTP-5E or higher level	
Performance	Processing Type: Store and Forward Transmission Mode: half/full-duplex with auto-negotiation function MAC Table Size: 4K Buffer Space: 448K Back bandwidth: 16G	



	Time Delay: <150µs	
Power	Power type: external power supply	
	Connector: DC Socket	
	Working Voltage: 5V	
Environment	Storage Temperature: -40 \sim 70 $^\circ\mathrm{C}$	
	Operating Temperature: -10 \sim 55 $^\circ\!\mathrm{C}$	
	Relative Humidity: 5-90% (no condensation)	
Warranty	1 year	
MTBF	50,000 hours	
Physical Characteristics	Dimension: 120×50×22mm	
	Weight:	
	Color: White	