



GLISS[®] GEL

TECHNICAL INFORMATION

GLISS[®] GEL is designed to eliminate the friction existing when heavy power cables are installed in plastic ducts.

GLISS[®] GEL eliminates up to 80% of friction; its potential applications are in the same fields as have already been solved by lubricants in the same series, and specifically where problems cannot be entirely solved using previous products.

Appearance: the product is a clear blue gel; the water and glycol in the gelatin act as lubricants as well as vehicles for other specific lubricants which act where greater friction would prevent proper cable installation.

In civil installation applications, the product helps prevent **unwanted spilling** of the lubricant on wooden floors, carpets, and in general on any material that is difficult to clean.

In industrial applications, it is used for laying large-section **power cables** inside plastic or concrete ducts.

Use: apply the gel on the cable with a sponge; install cable.

The water will evaporate, leaving a layer of lubricant on the cable.

The lubricant layer will stay on for a very long time, facilitating replacement or introduction of other cables in the same duct.

No glue effect (the glue effect occurs when, once the water evaporates, the gel turns into glue, causing all the cables to stick to each other).

GLISS[®] GEL is a non-toxic, inert, bio-degradable, non-flammable product.

TECHNICAL SPECIFICATIONS

Appearance	clear blue gel
Odor	none
Viscosity	approx. 30,000 cp
Specific gravity	gr/cm ³ 1
pH	7 neutral
Use temperature	- 15 - + 50 C°
Toxicity	non-toxic
WGK	1 (according to 2000 German and British standards)

PACKAGING:

Cod VGEL 1	Cardboard box containing 1kg bottles 15 units
Cod VGEL 5 15 25	5 15- 25 kg buckets