



Easy Network, Trustable

300Mbps Wireless N Router

WF2409E



Features:

Incredible wireless high speed up to 300Mbps, great for faster downloading, Internet calling and HD video streaming

MIMO high gain 5dBi antennas providing maximum range and stable connections

Dual operation modes- Router, Bridge (pure access point)

Various WAN connection types in AP Router mode- DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP

Multiple wireless modes- AP, Repeater, AP+WDS, WDS, Client

Multi-SSID providing up to 3 additional separate networks for guests and friends

Easy wireless security setup at a push of the WPS button

Intelligent bandwidth control to manage the bandwidth usage for each computer reasonably

Internet Access Control- IP filtering, MAC Filtering, Domain Filtering based on time

Quick setup, with built-in multilingual management page

What it does:

The netis router WF2409E offers 300Mbps high speed to connect your computers, smartphones, wireless cameras and other Wi-Fi devices. Bundled with three 5dBi high gain antennas, it ensures a better wireless coverage and allows you to enjoy the wireless freedom anywhere around your home, ideal for faster downloading, Internet calling and HD video streaming.

Specification:

Wireless		
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	
Signal Rate	Up to 300Mbps	
Frequency Range	2.4-2.4835GHz	
Transmit Power	20dBm(MAX)	
Data Transfer Rate	802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense) 801.11g:(54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b:(11Mbps,9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)	
Wireless Mode	AP, WDS, AP+WDS, Repeater, Client, Multi-SSID	
Wireless Security	64/128-bit WEP SSID Broadcast Enable/Disable	WPA-PSK/WPA2-PSK(TKIP/AES) Wireless MAC Filtering
Hardware		
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX	
Interfaces	1 * 10/100M Auto MDI/MDIX RJ45 WAN port 4 * 10/100M Auto MDI/MDIX RJ45 LAN port	
LED Indicators	PWR, WLAN, LAN1-LAN4, WAN, WPS	
Buttons	Default, WPS	
Antennas	3* 5dBi Fixed Antenna	
Power Supply	DC 9V/500mA(Output)	
Software		
WAN Type	DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WISP	
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port	
QoS	WMM, Bandwidth Control	
Access Control	IP/MAC/Domain filtering	
VPN Pass-through	PPTP, L2TP, IPSEC	
Others	IPTV, Dynamic DNS, Static Routing, WOL, Backup & Restore, Firmware Upgrade	
Others		
Certification	FCC, CE	
Environment	Operating Temperature: 0°C~40°C Operating Humidity: 10%~90% non-condensing	Storage Temperature: -40°C~70°C Storage Humidity: 5%~90% non-condensing
Package	1 * WF2409E 1 * Ethernet Cable	1 * 9V/500mA Power Adapter 1 * Quick Installation Guide(Multilingual)

Topological Graph:

